



Exhaust series Atmos



Description	Atmos Compact	Atmos Mono	Atmos Mono plus	Atmos Duo plus
Housing DxWxH	675x815x555/520mm	700x560x1050mm		
Connection voltage	230V/50/60 Hz 115V/50/60 Hz			230V/50/60 Hz
Nominal current	8 A (230V) 11,9 A (115V)	8,4 A (230V) 11,9 A (115V)		16 A
Electrical power	1,2 kW (230V) 0,8 kW (115V)			2,4 kW
Motor	1 pc. Permanent-rotor motor			2 pcs. Permanent-rotor motors
Max. airflow	250m ³ /h	320m ³ /h		2x 320m ³ /h
Negative pressure	8.500 Pa (230V) 5.800 Pa (115V)			8.500 Pa
Filter type	Pocket-compact filter	Compact filter		
Filter material	Synthetic-Fiber			
Activated carbon	1 pc. Activated carbon filter	1 pc. Comfort Carbon bag	2 pcs. Comfort Carbon bags	2 pcs. Comfort Carbon bags
Hose connection 1	NW 77,5			
Hose connection 2	NW 50			
Controller	Membrane keyboard incl. digital display showing filter saturation, airflow, operating hours or speed value			
Surrounding conditions	+5 °C to +35 °C, indoor, relative humidity of max. 65%, no condensation on equipment surface permitted, vibration-free, dust-free			

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE



www.troteclaser.com

Trotec Produktions- und Vertriebs GmbH_Linzer Strasse 156, A-4600 Wels, Austria,

tel_+43 (0)7242 239-0, fax_+43 (0)7242 239-7380, mailto:trotec@troteclaser.com, http://www.troteclaser.com

Oberbank Wels. BLZ 15130. Konto 961-0048/27. SWIFT: OBKLAT 2 LWEL. DVR0939838, FN164144p b LG Wels, UID.Nr. ATU43666001